

SWASTIK Group Company

ARM STITCH™

FIBC/BIG BAG SEWING MACHINE



AS-602 HR

AS - 602 HR

TECHNICAL DETAIL:

SINGLE NEEDLE, PLAIN FEED, FLAT BED, DOUBLE THREAD, OVERSEAMING (HIRACLE) SEWING MACHINE.

APPLICATION:

For Over Edging (Hiracle) Stitch on Light to Heavy Weight Fabric Such As PP/HDPE Woven Cloth, Big Bags, FIBC, Jute.



AS-602 UHR

AS - 602 UHR

TECHNICAL DETAIL:

SINGLE NEEDLE, DOUBLE THREAD, OVERSEAMING (HIRACLE) SEWING MACHINE WITH LOWERFEED & ALTERNATING UPPERFEED.

APPLICATION:

For Even Matched Seams. Over Edging On Container Bags Made From Woven Polypropylene With Polypropylene Threads (Over Seam Width Max. 18 mm) (Filler Cord From Top & Below Can Be Stitched For Sealing Needle Punctures).

TECHNICAL PARAMETERS:

MODEL	MAX. SPEED (R.P.M.) APPROX.	WORKING SPEED (R.P.M.) APPROX.	STITCH RANGE (100 MM)	OVER-SEAM WIDTH (MM)	SEWING CAPACITY (MM)	NEEDLE SIZE	NO. OF NEEDLES	NO. OF THREAD	STITCHING THREAD TYPE	LUBRI-CATION	MOTOR
AS 602 HR	2000	1800 depends on Sewing Material	7 - 13 * Adjus-table	Up to 15 mm	Up to 12 mm	DR X 4 # 32 (Organ)	One	Two	Jute, PP Multi Filament, Fabricated Yarn	Semi Auto-matic	1 H.P., 1 or 3 phase 1425-2850 RPM
AS 602 UHR	1800	1600 depends on Sewing Material	6 - 13 * Adjus-table	Up to 18 mm	Up to 15 mm	UY9853G 430/34, 400/33 (Singer)	One	Two	Multi Filament, Fabricated Yarn	Semi Auto-matic	1 H.P., 1 or 3 phase 1425-2850 RPM

Mfg. =



SWASTIK ENTERPRISE

PLOT NO-46, ROAD NO-2, GIDC, KATH WADA, AHMEDABAD-382430 - GUJARAT, INDIA

Phone : +91-079-29701398 Mobil e : +91-9426051346, 9879795395

E-mail : svastik@yahoo.com,swastik_2000@hotmail.com Website : www.circularloomspares.com